

SHARP®

The 30" LCD TELEVISION

LC-30HV2E



Specifications for LC30HV2E LCD Display

Screen Size (H x W) 30" (384.76 x 643.2 mm) with diagonal of 75 cm
Drive System TFT (thin-film transistor) active-matrix drive system
Pixel Count 2,949,120 dots (1280V x 3 x 768H)
Screen Brightness 450 cd/m2

Contrast Ratio : 500:1

Viewing Angle : Vertical 170°, Horizontal 170°

Backlight Source : Internal (built-in fluorescent tube)

TV Reception Channels PAL B/G, D/K, I SECAM B/G, D/K, L UHF/VHF/Hyperband

Audio NICAM/1 GR 2 x10 WRMS

Rear Terminals Antenna Input 75Ω, 3x Scart, Component (RCA), Audio out, Monitor out inc. S-Video Display output x 2, RS232 x 1

Front Terminals Analogue RGB in, PC Audio in, S-Video in, AV Input (RCA)

Power Supply 220V - 240V AC

Power Consumption TBC

Standby Power Consumption TBC

External Dimensions (W x D x H)

Display Section Only 766 x 79 x 497 mm

With Speaker Sections Attached 1002 x 84.5 x 497 mm

With Speaker Sections Attached and Mounted on Table Stand*6 1002 x 305 x 597 mm

Weight (approx.)

Display Section Only 14.0 kg

With Speaker Sections Attached 16.8 kg

With Speaker Sections Attached and Mounted on Table Stand*6 19.9 kg

Accessories Power cord. Table stand (with main unit already mounted). Wireless Remote Control. AAA dry battery (2).

Antenna cable. Wireless AV signal receiver mounting stand. Wall-mount spacer. Operation manual